



Š izbrani izdelek.



ASUS ROG RAPTURE GT-AX6000 GAMING WIFI 6 DUAL-BAND AX6000 BREŽŽIČNI USMERJEVALNIK, 802.11A/B/G/N/AC/AX, 4804MBPS+1148MBPS

ŠIFRA: ASUNC-ROG_GTAX600

231.99€

ROG Rapture GT-AX6000 ASUS 4711081394549

DODATNE INFORMACIJE

Weight 1.5000 kg

**Garancija
mesecev** 36 mesecev

Proizvajalec ASUS



Zaloga: 2 na zalogi

Kategorije: [Mrežna oprema](#), [Usmerjevalniki](#)



OPIS IZDELKA

Podprti standardi: IEEE 802.11a, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n, IEEE 802.11ac, IEEE 802.11ax, IPv4, IPv6

Frekvenca:



2.4GHz AX: 4x4 (Tx/Rx) 1024 QAM 20/40MHz, up to 1148Mbps

Vaš izbrani izdelek.

5GHz AX: 4x4 (Tx/Rx) 1024 QAM 20/40/80/160MHz, up to 4804Mbps

Hitrost:

Žična:

4 x RJ45 Gigabits BaseT

1 x RJ45 for 2.5 Gigabits BaseT

Brezžična:

2.4GHz AX: 4x4 (Tx/Rx) 1024 QAM 20/40MHz, up to 1148Mbps

5GHz AX: 4x4 (Tx/Rx) 1024 QAM 20/40/80/160MHz, up to 4804Mbps

Antena: 4 x zunanja

Zaščite: Open system, WPA/WPA2/WPA3-Personal, WPA/WPA2-Enterprise

Priključki:

1 x RJ45 for 2.5 Gigabits BaseT for WAN/LAN

1 x RJ45 for 2.5 Gigabits BaseT for LAN

4 x RJ45 for Gigabits BaseT for LAN

1 x USB 3.2 Gen1

1 x USB 2.0

Funkcije: Game Boost/acceleration, ROG_First, OpenNAT (Game Profile), Gaming port, AiProtection Pro, Router Security Assessment, Malicious site blocking, Two-Way IPS, Infected Device Prevention and Blocking, Parental Control, Parental Control Customized Internet schedule

Dimenzije:

Teža: 1,1kg

Dodatno:

OFDMA (Orthogonal Frequency Division Multiple Access)

Beamforming: standard-based and universal

1024-QAM high data rate

20/40/80/160 MHz bandwidth

WPS Button, Reset Button, Power Button, LED Control Button

AiMesh

Primary AiMesh router

AiMesh node

Adaptive QoS

Bandwidth Monitor

Bandwidth limiter

Maximum Bandwidth limiter rule : 32

Traditional QoS

Maximum Traditional QoS rule : 32



Traffic Monitor

Vas izbrani izdelek.

Real-time traffic monitor

Wired Traffic Monitor

Wireless Traffic Monitor

Traffic Analyzer

Traffic analysis period : Daily, Weekly, Monthly

Website history

IPv6

MU-MIMO

WiFi Encryption : Open system, WPA/WPA2/WPA3-Personal, WPA/WPA2-Enterprise

UTF-8 SSID

Guest Network

Maximum Guest Network rule : 2.4GHz x3, 5GHz x3

Guest Network Connection time limit

Guest Network Encryption : Open system, WPA/WPA2/WPA3-Personal

WPS

Wi-Fi MAC address filter

Maximum MAC filters : 64

Wireless scheduler

Airtime fairness

RADIUS Server

Universal beamforming

Explicit beamforming

Internet connection Type : PPPoE, PPTP, L2TP, Automatic IP, Static IP

Dual WAN

WAN Aggregation

3G/4G LTE dongle

Android tethering

Port forwarding

Maximum port forwarding rule : 64

Port triggering

Maximum port triggering rule : 32

DMZ

DDNS

NAT Passthrough : PPTP, L2TP, IPSec, RTSP, H.323, SIP Passthrough, PPPoE relay

DHCP Server

IGMP snooping



IPTV

Vaš izbrani izdelek.

LAN Link Aggregation

Manually assign IP address

Maximum manually assign IP address rule : 64

VPN Client L2TP

VPN Client OVPN

VPN Client PPTP

VPN Server IPsec

VPN Server OVPN

VPN Server PPTP

VPN Fusion

File System : HFS+, NTFS, vFAT, ext2, ext3, ext4

HDD hibernation

Safely Remove disk

AiCloud

Download master

AiDisk

Media Server

Time Machine

Samba Server

FTP Server

Shared Folder privileges

Operating mode : Accesspoint, AiMeshnode, Mediabridge, Repeater, Router

Operating system : ASUSWRT

Free OS upgrade

Firewall

Maximum Firewall keyword filter : 64

Maximum Firewall network service filter : 32

Maximum Firewall URL filter : 64

Wake on LAN (WOL)

SSH

Configuration backup and restore

Diagnosis tools

Feedback system

System log

Uradna stran proizvajalca: <https://rog.asus.com/networking/rog-rapture-gt-ax6000-model/>



Vaš izbrani izdelek.