



Vaš izbrani izdelek.



GIGABYTE B550 AORUS ELITE V2, DDR4, SATA3, USB3.2GEN2, DP, 2.5GBE, AM4 ATX

ŠIFRA: GIGMB-B550AORUSEV2_3
151.99€

B550 AORUS ELITE V2 GIGABYTE 4719331809898

DODATNE INFORMACIJE

Weight	1.1000 kg
Dimensions	26.5 × 7 × 7 cm
Garancija mesecih	36 mesecev
Proizvajalec	GIGABYTE



Zaloga: 10 na zalogi

Kategorije: [Osnovne plošče](#), [Računalniške komponente](#), [Računalništvo](#)



Vaš izbrani izdelek.



OPIS IZDELKA

PODNOŽJE: AMD AM4

ZA PROCESORJE: AMD RYZEN

FORMAT: ATX format 30.5 cm x 24.4 cm

VEZNI ČIP: AMD B550

POMNILNIK:

4 x DDR4 DIMM ECC/non-ECC do 4733(O.C.) / 4600(O.C.) / 4400(O.C.) / 4266(O.C.) / 4133(O.C.) / 4000(O.C.) / 3866(O.C.) / 3733(O.C.) / 3600(O.C.) / 3466(O.C) / 3400(O.C.) / 3200 / 2933 / 2667 / 2400 / 2133 MHz (odvisno od procesorja) do skupno 128GB kapacitete, dual channel in Extreme Memory Profile (XMP) podpora

GRAFIKA: DA - preko APU

RAID: DA (0,1,10)

RAZŠIRITVENE REŽE:

1 x PCI Express x16 slot (PCIEX16), integrated in the CPU:

- AMD Ryzen™ 5000 Series and Ryzen™ 3000 Series Processors support PCIe 4.0 x16 mode
- AMD Ryzen™ Ryzen™ 5000 G-Series and Ryzen™ 4000 G-Series Processors support PCIe 3.0 x16 mode

* For optimum performance, if only one PCI Express graphics card is to be installed, be sure to install it in the PCIEX16 slot.

1 x PCI Express x16 slot (PCIEX2), integrated in the Chipset:

- Supporting PCIe 3.0 x2 mode

1 x PCI Express x16 slot (PCIEX1_2), integrated in the Chipset:

- Supporting PCIe 3.0 x1 mode

1 x PCI Express x1 slot (PCIEX1_1), integrated in the Chipset:

- Supporting PCIe 3.0 x1 mode

MREŽNA KARTICA: Realtek 2.5GbE LAN chip (10/100/1000Mbit/2.5Gbit)



ZVOČNA KARTICA: Realtek ALC1200-VB codec High Definition Audio (2/4/5.1/7.1-channel)

Vaš izbrani izdelek.

NOTRANJI PRIKLJUČKI:

- 1 x 24-pin ATX main power connector
- 1 x 8-pin ATX 12V power connector
- 2 x M.2 Socket 3 connectors
- 4 x SATA 6Gb/s connectors
- 1 x CPU fan header
- 1 x water cooling CPU fan header
- 3 x system fan headers
- 1 x CPU cooler LED strip/RGB LED strip header
- 2 x addressable LED strip headers
- 2 x RGB LED strip headers
- 1 x front panel header
- 1 x front panel audio header
- 1 x USB Type-C™ port, with USB 3.2 Gen 1 support
- 1 x USB 3.2 Gen 1 header
- 2 x USB 2.0/1.1 headers
- 1 x Trusted Platform Module (TPM) header (2x6 pin, for the GC-TPM2.0_S module only)
- 1 x Clear CMOS jumper

ZUNANJI PRIKLJUČKI:

- 1 x DisplayPort
- 1 x HDMI port
- 2 x USB 3.2 Gen 2 Type-A ports (red)
- 3 x USB 3.2 Gen 1 ports
- 2 x USB 2.0/1.1 ports
- 1 x Q-Flash Plus button
- 1 x RJ-45 port
- 1 x optical S/PDIF Out connector
- 5 x audio jacks

DODATNO:

- iTE® I/O Controller Chip
- H/W Monitoring
- Voltage detection
- Temperature detection
- Fan speed detection
- Water cooling flow rate detection



Overheating warning

Vaš izbrani izdelek.

Fan fail warning

Fan speed control

BIOS

1 x 256 Mbit flash

Use of licensed AMI UEFI BIOS

PnP 1.0a, DMI 2.7, WfM 2.0, SM BIOS 2.7, ACPI 5.0

Unique Features

Support for APP Center

@BIOS

EasyTune

Fast Boot

Game Boost

ON/OFF Charge

RGB Fusion

Smart Backup

System Information Viewer

Support for Q-Flash Plus

Support for Q-Flash

Support for Xpress Install

Bundled Software

Norton® Internet Security (OEM version)

Realtek® 8125 Gaming LAN Bandwidth Control Utility

Spletna stran proizvajalca: <https://www.gigabyte.com/Motherboard/B550-AORUS-ELITE-V2-rev-15#kf>