



Vaš izbrani izdelek.



**GIGABYTE B650 AERO G, DDR5, SATA3,
USB3.2GEN2X2, DP, 2.5GBE, WIFI 6E, AM5 ATX**

ŠIFRA: GIGMB-B650AEROG
332.99€

B650 AERO G GIGABYTE 4719331848972

DODATNE INFORMACIJE

Weight 1.0000 kg

Dimensions 7 × 26.5 × 26.5 cm

**Garancija
mesecih** 36 mesecev

Proizvajalec GIGABYTE



Zaloga: 6 na zalogi

Kategorije: [Osnovne plošče](#), [Računalniške komponente](#),
[Računalništvo](#)





OPIS IZDELKA

PODNOŽJE: AMD AM5

ZA PROCESORJE: AMD RYZEN 7000/8000 Series

FORMAT: ATX format 30.5 cm x 24.4 cm

VEZNI ČIP: AMD B650

POMNILNIK:

4 x DDR5 DIMM non-ECC 8000(OC)/ 7800(OC)/ 7600(OC)/ 7200(OC)/ 7000(OC)/ 6800(OC)/ 6666(OC)/ 6600(OC)/ 6400(OC)/ 6200(OC)/ 6000(OC)/ 5600(OC)/ 5200/ 4800/ 4400MHz (odvisno od procesorja) do skupno 192GB kapacitete, dual channel in EXtended Profiles for Overclocking, Extreme Memory Profile (XMP) podpora

GRAFIKA: DA - preko APU

RAID: DA (0,1,10)

RAZŠIRITVENE REŽE:

CPU:

1 x PCI Express x16 slot, supporting PCIe 4.0 and running at x16 (PCIEX16)

Chipset:

1 x PCI Express x16 slot, supporting PCIe 4.0 and running at x4 (PCIEX4)

1 x PCI Express x16 slot, supporting PCIe 3.0 and running at x1 (PCIEX1)

Support for AMD CrossFire™ technology (PCIEX16 and PCIEX4)

MREŽNA KARTICA: Intel 2.5GbE LAN chip (10/100/1000Mbit/2.5Gbit) ; AMD Wi-Fi 6E RZ616, a, b, g, n, ac, ax, supporting 2.4/5/6 GHz, BLUETOOTH 5.2

ZVOČNA KARTICA: Realtek ALC1220-VB CODEC Audio High Definition Audio (2/4/5.1/7.1-channel)

NOTRANJI PRIKLJUČKI:

1 x 24-pin ATX main power connector

1 x 8-pin ATX 12V power connector

1 x 4-pin ATX 12V power connector



1 x CPU fan header

Vaš izbrani izdelek.

1 x water cooling CPU fan header

4 x system fan headers

2 x system fan/water cooling pump headers

2 x addressable LED strip headers

2 x RGB LED strip headers

1 x CPU cooler LED strip/RGB LED strip header

3 x M.2 Socket 3 connectors

4 x SATA 6Gb/s connectors

1 x front panel header

1 x front panel audio header

1 x USB Type-C® header, with USB 3.2 Gen 2x2 support

1 x USB 3.2 Gen 1 header

2 x USB 2.0/1.1 headers

1 x noise detection header

1 x THB_U4 add-in card connector

1 x Trusted Platform Module header (For the GC-TPM2.0 SPI/GC-TPM2.0 SPI 2.0 module only)

1 x serial port header

1 x Q-Flash Plus button

1 x reset button

1 x reset jumper

2 x temperature sensor headers

1 x Clear CMOS jumper

ZUNANJI PRIKLJUČKI:

2 x SMA antenna connectors (2T2R)

2 x USB 2.0/1.1 ports

1 x DisplayPort In port

1 x HDMI port

3 x USB 3.2 Gen 2 Type-A ports (red)

1 x USB Type-C® port (DisplayPort), with USB 3.2 Gen 2 support

4 x USB 3.2 Gen 1 ports

1 x RJ-45 port

2 x audio jacks

1 x optical S/PDIF Out connector

DODATNO:

ITE® I/O Controller Chip



H/W Monitoring

Vas izbrani izdelek.

Voltage detection

Temperature detection

Fan speed detection

Water cooling flow rate detection

Fan fail warning

Fan speed control

Noise detection

BIOS

1 x 256 Mbit flash

Use of licensed AMI UEFI BIOS

PnP 1.0a, DMI 2.7, WfM 2.0, SM BIOS 2.7, ACPI 5.0

Unique Features

Support for GIGABYTE Control Center (GCC)

Support for Q-Flash

Support for Q-Flash Plus

Bundled Software

Norton® Internet Security (OEM version)

LAN bandwidth management software

Spletna stran proizvajalca: <https://www.gigabyte.com/Motherboard/B650-AERO-G-rev-10#kf>