



Vaš izbrani izdelek.



GIGABYTE B650 AORUS ELITE AX ICE, DDR5, SATA3, USB3.2GEN2X2, DP, 2.5GBE, WIFI 6E, AM5 ATX

ŠIFRA: GIGMB-B650AELITEAXI

290.99€

B650 AORUS ELITE AX ICE GIGABYTE 4719331859374


DODATNE INFORMACIJE

Weight	1.1000 kg
Dimensions	26.5 × 7 × 7 cm
Garancija mesecev	36 mesecev
Proizvajalec	GIGABYTE



Zaloga: 1 na zalogi

Kategorije: [Osnovne plošče](#), [Računalniške komponente](#),
[Računalništvo](#)





Vaš izbrani izdelek.

OPIS IZDELKA

PODNOŽJE: AMD AM5

ZA PROCESORJE: AMD RYZEN 7000/8000 Series

FORMAT: ATX format 30.5 cm x 24.4 cm

VEZNI ČIP: AMD B650

POMNILNIK:

4 x DDR5 DIMM non-

ECC 8000(OC)/7800(OC)/7600(OC)/7200(OC)/7000(OC)/6800(OC)/6666(OC)/6600(OC)/6400(OC)/6200(OC)/6000(OC)/5600(OC)/5200/4800/4400MHz (odvisno od procesorja) do skupno 192GB kapacitete, dual channel in EXTENDED Profiles for Overclocking, Extreme Memory Profile (XMP) podpora

GRAFIKA: DA - preko APU

RAID: DA (0,1,10) support for SATA/NVME storage devices

RAZŠIRITVENE REŽE:

1 x PCI Express x16 slot (PCIEX16), integrated in the CPU:

- AMD Ryzen™ 7000 Series Processors support PCIe 4.0 x16 mode

- AMD Ryzen™ 8000 Series-Phoenix 1 Processors support PCIe 4.0 x8 mode

- AMD Ryzen™ 8000 Series-Phoenix 2 Processors support PCIe 4.0 x4 mode

* The PCIEX16 slot can only support a graphics card or an NVMe SSD. If only one graphics card is to be installed, be sure to install it in the PCIEX16 slot.

Chipset:

- 2 x PCI Express x16 slots, supporting PCIe 3.0 and running at x1 (PCIEX1_1/2)

MREŽNA KARTICA: Realtek 2.5GbE LAN chip (10/100/1000Mbit/2.5Gbit) ; Realtek Wi-Fi 6E RTL8852CE, a, b, g, n, ac, ax, supporting 2.4/5/6 GHz, BLUETOOTH 5.3

ZVOČNA KARTICA: Realtek Audio codec High Definition Audio (2/4/5.1/7.1-channel)

NOTRANJI PRIKLJUČKI:

1 x 24-pin ATX main power connector

1 x 8-pin ATX 12V power connector

1 x 4-pin ATX 12V power connector

1 x CPU fan header

1 x CPU fan/water cooling pump header

3 x system fan headers

1 x system fan/water cooling pump header

3 x addressable RGB Gen2 LED strip headers



1 x RGB LED strip header
Vaš izbrani izdelek.
3 x M.2 Socket 3 connectors
4 x SATA 6Gb/s connectors
1 x front panel header
1 x front panel audio header
1 x USB Type-C® header, with USB 3.2 Gen 2x2 support
1 x USB 3.2 Gen 1 header
2 x USB 2.0/1.1 headers
1 x Trusted Platform Module header (For the GC-TPM2.0 SPI/GC-TPM2.0 SPI 2.0/GC-TPM2.0 SPI V2 module only)

1 x reset button

1 x reset jumper

1 x Clear CMOS jumper

ZUNANJI PRIKLJUČKI:

1 x Q-Flash Plus button

2 x SMA antenna connectors (2T2R)jk

1 x DisplayPort

1 x HDMI port

1 x USB Type-C® port, with USB 3.2 Gen 2 support

2 x USB 3.2 Gen 2 Type-A ports (red)

5 x USB 3.2 Gen 1 ports

4 x USB 2.0/1.1 ports

1 x RJ-45 port

3 x audio jacks

DODATNO:

iTE® I/O Controller Chip

H/W Monitoring

Voltage detection

Temperature detection

Fan speed detection

Water cooling flow rate detection

Fan fail warning

Fan speed control

BIOS

1 x 256 Mbit flash

Use of licensed AMI UEFI BIOS



PnP 1.0a, DMI 2.7, WfM 2.0, SM BIOS 2.7, ACPI 5.0

Vaš izbrani izdelek.

Unique Features

Support for GIGABYTE Control Center (GCC)

Support for Q-Flash

Support for Q-Flash Plus

Bundled Software

Norton® Internet Security (OEM version)

LAN bandwidth management software

Spletna stran proizvajalca: <https://www.gigabyte.com/Motherboard/B650-AORUS-ELITE-AX-ICE#kf>