



Vaš izbrani izdelek.



GIGABYTE X670 AORUS ELITE AX, DDR5, SATA3, USB3.2GEN2X2, DP, WIFI, AM5 ATX

ŠIFRA: GIGMB-X670AELAX_2
329.99€

X670 AORUS ELITE AX GIGABYTE 4719331848798


DODATNE INFORMACIJE

Weight	1.6700 kg
Dimensions	8 × 33.4 × 33.4 cm
Garancija mesecih	36 mesecev
Proizvajalec	GIGABYTE



Zaloga: 10 na zalogi

Kategorije: [Osnovne plošče](#), [Računalniške komponente](#), [Računalništvo](#)





Vaš izbor



OPIS IZDELKA

PODNOŽJE: AMD AM5

ZA PROCESORJE: AMD Socket AM5 for AMD Ryzen™ 7000 Series Desktop Processors

FORMAT: ATX format 30.5 cm x 24.4 cm

VEZNI ČIP: AMD X670

POMNILNIK:

4 x DIMM, Max. 128GB, DDR5 6666(OC) / 6600(OC) / 6400(OC) / 6200(OC) / 6000(OC) / 5600(OC) / 5200 / 4800 / 4400MHz non-ECC Un-buffered DIMM 1Rx8/2Rx8/1Rx16 memory modules

Dual Channel Memory Architecture

Supports AMD Extended Profiles for Overclocking (EXPO™)

Extreme Memory Profile (XMP) memory modules

GRAFIKA: preko APU, če le-ta podpira

RAID: DA (0,1,10) support for SATA / NVMe SSD storage devices

RAZŠIRITVENE REŽE:

1 x PCI Express x16 slot, supporting PCIe 4.0 and running at x16 (PCIEX16)

1 x PCI Express x16 slot, supporting PCIe 4.0 and running at x4 (PCIEX4)

1 x PCI Express x16 slot, supporting PCIe 3.0 and running at x2 (PCIEX2)

MREŽNA KARTICA: Realtek 2.5GbE LAN chip + AMD Wi-Fi 6E RZ616 (MT7922A22M) WIFI a, b, g, n, ac, ax + BLUETOOTH 5.2

ZVOČNA KARTICA: Realtek 7.1 Surround Sound High Definition Audio CODEC

NOTRANJI PRIKLJUČKI:

1 x 24-pin ATX main power connector

2 x 8-pin ATX 12V power connectors

1 x CPU fan header

1 x water cooling CPU fan header

3 x system fan headers



1 x CPU cooler LED strip/RGB LED strip header

Vas izbrani izdelek.

2 x addressable LED strip headers

2 x RGB LED strip headers

4 x SATA 6Gb/s connectors

4 x M.2 Socket 3 connectors

1 x front panel header

1 x front panel audio header

1 x USB Type-C® header, with USB 3.2 Gen 2x2 support

2 x USB 3.2 Gen 1 headers

2 x USB 2.0/1.1 headers

1 x THB_U4 add-in card connector

1 x Trusted Platform Module header (For the GC-TPM2.0 SPI/GC-TPM2.0 SPI 2.0 module only)

1 x power button

1 x reset button

1 x Clear CMOS button

1 x reset jumper

1 x Clear CMOS jumper

ZUNANJI PRIKLJUČKI:

1 x Q-Flash Plus button

2 x SMA antenna connectors (2T2R)

1 x HDMI port

6 x USB 3.2 Gen 1 ports

4 x USB 2.0/1.1 ports

2 x USB 3.2 Gen 2 Type-A ports (red)

1 x USB Type-C® port, with USB 3.2 Gen 2x2 support

1 x RJ-45 port

3 x audio jacks

DODATNO:

iTE® I/O Controller Chip

H/W Monitoring

Voltage detection

Temperature detection

Fan speed detection

Water cooling flow rate detection

Fan fail warning

Fan speed control



BIOS

Vas izbrani izdelek.

1 x 256 Mbit flash

Use of licensed AMI UEFI BIOS

PnP 1.0a, DMI 2.7, WfM 2.0, SM BIOS 2.7, ACPI 5.0

Unique Features

Support for GIGABYTE Control Center (GCC)

Support for Q-Flash

Support for Q-Flash Plus

Support for Smart Backup

Bundled Software

Norton® Internet Security (OEM version)

LAN bandwidth management software

Spletna stran

proizvajalca: <https://www.gigabyte.com/Motherboard/X670-AORUS-ELITE-AX-rev-10-12#kf>