



Š izbrani izdelek.



GIGABYTE Z790 AERO G, DDR5, SATA3, USB3.2GEN2X2, DP, 2.5GBE, WIFI 6E, LGA1700 ATX


ŠIFRA: GIGMB-Z790_AEROG

378.99€

Z790 AERO G GIGABYTE 4719331849610

DODATNE INFORMACIJE

Weight	1.5600 kg
Dimensions	8.5 × 34.5 × 34.5 cm
Garancija mesecev	36 mesecev
Proizvajalec	GIGABYTE



Zaloga: 1 na zalogi

Kategorije: [Osnovne plošče](#), [Računalniške komponente](#),
[Računalništvo](#)



OPIS IZDELKA



PODNOŽJE: INTEL LGA1700

Vaš izbrani izdelek.

ZA PROCESORJE: Intel 12/13th Generation Core™ i7/i5/i3/Pentium/Celeron

FORMAT: ATX Form Factor 30.5 x 24.4 cm

VEZNI ČIP: Intel Z790 Express

POMNILNIK:

4 x DDR5 (7600(O.C.) /7400(O.C.) /7200(O.C.) /7000(O.C.) /6800(O.C.) /6600(O.C.) / 6400(O.C.) / 6200(O.C.) / 6000(O.C.) / 5800(O.C.) / 5600(O.C.) / 5400(O.C.) / 5200(O.C.) / 4800 / 4000MHz) do skupno 128GB kapacitete, dual channel in Extreme Memory Profile (XMP) podpora, Support for non-ECC / ECC Un-buffered DIMM (operate in non-ECC mode), Support for ECC Un-buffered DIMM 1Rx8/2Rx8 memory modules (operate in non-ECC mode), Support for non-ECC Un-buffered DIMM 1Rx8/2Rx8/1Rx16 memory modules

GRAFIKA: preko CPU

RAID: DA (0,1,5,10)

RAZŠIRITVENE REŽE:

1 x PCIe 5.0/4.0/3.0 x16 (x16 mode)

2 x PCIe 3.0 x16 (x4 mode)

MREŽNA KARTICA: Intel 2.5GbE LAN chip (2.5 Gbps/1 Gbps/100 Mbps) + Wi-Fi 6E AX211 WIFI a, b, g, n, ac, ax, supporting 2.4/5/6 GHz + BLUETOOTH 5.3

ZVOČNA KARTICA: Realtek® ALC1220-VB High Definition Audio Audio CODEC

NOTRANJI PRIKLJUČKI:

1 x 24-pin ATX main power connector

1 x 8-pin ATX 12V power connector

1 x 4-pin ATX 12V power connector

1 x CPU fan header

1 x water cooling CPU fan header

4 x system fan headers

2 x system fan/water cooling pump headers

2 x addressable LED strip headers

2 x RGB LED strip headers

5 x M.2 Socket 3 connectors

4 x SATA 6Gb/s connectors

1 x front panel header

1 x front panel audio header

1 x USB Type-C® header, with USB 3.2 Gen 2x2 support

1 x USB 3.2 Gen 1 header

2 x USB 2.0/1.1 headers

1 x noise detection header



2 x Thunderbolt™ add-in card connectors

Vaš izbrani izdelek.

1 x Trusted Platform Module header (For the GC-TPM2.0 SPI/GC-TPM2.0 SPI 2.0 module only)

1 x serial port header

1 x Q-Flash Plus button

1 x reset button

1 x reset jumper

2 x temperature sensor headers

1 x Clear CMOS jumper

ZUNANJI PRIKLJUČKI:

2 x USB 2.0/1.1 ports

2 x SMA antenna connectors (2T2R)

4 x USB 3.2 Gen 1 ports

1 x DisplayPort In port

1 x HDMI 2.0 port

2 x USB 3.2 Gen 2 Type-A ports (red)

1 x USB Type-C® port, with USB 3.2 Gen 2x2 support

1 x USB Type-C® port (DisplayPort), with USB 3.2 Gen 2 support

1 x RJ-45 port

1 x optical S/PDIF Out connector

2 x audio jacks

DODATNO:

iTE® I/O Controller Chip

H/W Monitoring

Voltage detection

Temperature detection

Fan speed detection

Water cooling flow rate detection

Fan fail warning

Fan speed control

Noise detection

BIOS

1 x 256 Mbit flash

Use of licensed AMI UEFI BIOS

PnP 1.0a, DMI 2.7, WfM 2.0, SM BIOS 2.7, ACPI 5.0

Unique Features

Support for GIGABYTE Control Center (GCC)



Support for Q-Flash

Vas izbrani izdelek.

Support for Q-Flash Plus

Support for Smart Backup

Bundled Software

Norton® Internet Security (OEM version)

LAN bandwidth management software

Spletna stran proizvajalca: <https://www.gigabyte.com/Motherboard/Z790-AERO-G-rev-10#kf>