

Vaš izbrani izdelek.



## GIGABYTE Z790 AORUS PRO X, DDR5, SATA3, USB3.2GEN2X2, DP, PCI-E 5.0, 5GBE, WIFI 7, LGA1700 ATX

ŠIFRA: GIGMB-Z790APROX

465.99€

Z790 AORUS PRO X GIGABYTE 4719331857608

### DODATNE INFORMACIJE

<b>Weight</b>	1.5600 kg
<b>Dimensions</b>	27 × 8 × 8 cm
<b>Garancija mesecih</b>	36 mesecev
<b>Proizvajalec</b>	GIGABYTE



**Zaloga:** 3 na zalogi

**Kategorije:** [Osnovne plošče](#), [Računalniške komponente](#), [Računalništvo](#)





Vaš izbrani izdelek.

## OPIS IZDELKA

**PODNOŽJE:** INTEL LGA1700

**ZA PROCESORJE:** Intel 12/13/14th Generation Core™ i7/i5/i3/Pentium/Celeron

**FORMAT:** ATX Form Factor 30.5 x 24.4 cm

**VEZNI ČIP:** Intel Z790 Express

**POMNILNIK:**

4 x DDR5 (8266(O.C.) / 8200(O.C.) / 8000(O.C.) / 7950(O.C.) / 7900(O.C.) / 7800(O.C.) / 7600(O.C.) / 7400(O.C.) / 7200(O.C.) / 7000(O.C.) / 6800(O.C.) / 6600(O.C.) / 6400(O.C.) / 6200(O.C.) / 6000(O.C.) / 5800(O.C.) / 5600(O.C.) / 5400(O.C.) / 5200(O.C.) / 4800 / 4000MHz) do skupno 192GB kapacitete, dual channel in Extreme Memory Profile (XMP) podpora, Support for non-ECC / ECC Un-buffered DIMM (operate in non-ECC mode), Support for ECC Un-buffered DIMM 1Rx8/2Rx8 memory modules (operate in non-ECC mode), Support for non-ECC Un-buffered DIMM 1Rx8/2Rx8/1Rx16 memory modules

**GRAFIKA:** preko CPU

**RAID:** DA (0,1,5,10)

**RAZŠIRITVENE REŽE:**

1 x PCIe 5.0/4.0/3.0 x16 (x16 mode)

1 x PCIe 4.0 x16 (x4 mode)

1 x PCIe 3.0 x16 (x4 mode)

**MREŽNA KARTICA:** Realtek 5GbE LAN chip (5 Gbps/2.5 Gbps/1 Gbps/100 Mbps) + MediaTek Wi-Fi 7 MT7927, RZ738 802.11a, b, g, n, ac, ax, be, supporting 2.4/5/6 GHz + BLUETOOTH 5.3

**ZVOČNA KARTICA:** Realtek High Definition Audio Audio CODEC

**NOTRANJI PRIKLJUČKI:**

1 x 24-pin ATX main power connector

2 x 8-pin ATX 12V power connectors

1 x CPU fan header

1 x CPU fan/water cooling pump header

4 x system fan headers

2 x system fan/water cooling pump headers

3 x addressable RGB Gen2 LED strip headers

1 x RGB LED strip header

5 x M.2 Socket 3 connectors

4 x SATA 6Gb/s connectors



1 x front panel header

Vaš izbrani izdelek.

1 x front panel audio header

1 x USB Type-C® header, with USB 3.2 Gen 2x2 support

1 x USB Type-C® port (DisplayPort), with USB 2.0 support (Only available with the Intel® HD Graphics Processors.)

1 x USB 3.2 Gen 1 header

2 x USB 2.0/1.1 headers

1 x noise detection header

2 x Thunderbolt™ add-in card connectors

1 x Trusted Platform Module header (For the GC-TPM2.0 SPI/GC-TPM2.0 SPI 2.0/ GC-TPM2.0 SPI V2 module only)

1 x Q-Flash Plus button

1 x reset button

1 x reset jumper

2 x temperature sensor headers

1 x Clear CMOS jumper

**ZUNANJI PRIKLJUČKI:**

2 x USB 2.0/1.1 ports

2 x SMA antenna connectors (2T2R)

4 x USB 3.2 Gen 1 ports

1 x DisplayPort In port

1 x HDMI port

2 x USB 3.2 Gen 2 Type-A ports (red)

1 x USB Type-C® port, with USB 3.2 Gen 2x2 support

1 x USB Type-C® port (DisplayPort), with USB 3.2 Gen 2 support

1 x RJ-45 port

1 x optical S/PDIF Out connector

2 x audio jacks

**DODATNO:**

iTE® I/O Controller Chip

H/W Monitoring

Voltage detection

Temperature detection

Fan speed detection

Water cooling flow rate detection

Fan fail warning



Fan speed control

Vaš izbrani izdelek.

Noise detection

BIOS

1 x 256 Mbit flash

Use of licensed AMI UEFI BIOS

PnP 1.0a, DMI 2.7, WfM 2.0, SM BIOS 2.7, ACPI 5.0

Unique Features

Support for GIGABYTE Control Center (GCC)

Support for Q-Flash

Support for Q-Flash Plus

Support for Smart Backup

Bundled Software

Norton® Internet Security (OEM version)

LAN bandwidth management software

Spletna stran proizvajalca: <https://www.gigabyte.com/Motherboard/Z790-AORUS-PRO-X#kf>