



✓ Š izbrani izdelek.



GIGABYTE Z790 UD AX, DDR5, SATA3, USB3.2GEN2X2, DP, 2.5GBE, WIFI 6E, LGA1700 ATX

ŠIFRA: GIGMB-Z790_UDAX1

251.99€

Z790 UD AX GIGABYTE 4719331850395

DODATNE INFORMACIJE

Weight 1.0000 kg

**Garancija
mesech** 36 mesecev

Proizvajalec GIGABYTE



Zaloga: 1 na zalogi

Kategorije: [Osnovne plošče](#), [Računalniške komponente](#),
[Računalništvo](#)



OPIS IZDELKA

PODNOŽJE: INTEL LGA1700

ZA PROCESORJE: Intel 12/13th Generation Core™ i7/i5/i3/Pentium/Celeron



FORMAT: ATX Form Factor 30.5 x 24.4 cm

Vaš izbrani izdelek.

VEZNI ČIP: Intel Z790 Express

POMNILNIK:

4 x DDR5 (7600(O.C.) /7400(O.C.) /7200(O.C.) /7000(O.C.) /6800(O.C.) /6600(O.C.) / 6400(O.C.) / 6200(O.C.) / 6000(O.C.) / 5800(O.C.) / 5600(O.C.) / 5400(O.C.) / 5200(O.C.) / 4800 / 4000MHz) do skupno 128GB kapacitete, dual channel in Extreme Memory Profile (XMP) podpora, Support for non-ECC / ECC Un-buffered DIMM (operate in non-ECC mode), Support for ECC Un-buffered DIMM 1Rx8/2Rx8 memory modules (operate in non-ECC mode), Support for non-ECC Un-buffered DIMM 1Rx8/2Rx8/1Rx16 memory modules

GRAFIKA: preko CPU

RAID: DA (0,1,5,10) support for NVMe SSD storage devices

RAZŠIRITVENE REŽE:

CPU:

1 x PCI Express x16 slot, supporting PCIe 5.0 and running at x16 (PCIEX16)

* For optimum performance, if only one PCI Express graphics card is to be installed, be sure to install it in the PCIEX16 slot.

Chipset:

1 x PCI Express x16 slot, supporting PCIe 4.0 and running at x4 (PCIEX4)

1 x PCI Express x16 slot, supporting PCIe 3.0 and running at x1 (PCIEX1_4)

2 x PCI Express x1 slots, supporting PCIe 3.0 and running at x1 (PCIEX1_2, PCIEX1_3)

Support for AMD CrossFire™ technology (PCIEX16 and PCIEX4)

MREŽNA KARTICA: Realtek® 2.5GbE LAN chip (2.5 Gbps/1 Gbps/100 Mbps) + Intel Wi-Fi 6E AX210 a, b, g, n, ac, ax, supporting 2.4/5/6 GHz + BLUETOOTH 5.3

ZVOČNA KARTICA: Realtek® High Definition Audio Audio CODEC

NOTRANJI PRIKLJUČKI:

1 x 24-pin ATX main power connector

2 x 8-pin ATX 12V power connectors

1 x CPU fan header

1 x water cooling CPU fan header

3 x system fan headers

1 x system fan/water cooling pump header

2 x addressable LED strip headers

2 x RGB LED strip headers

3 x M.2 Socket 3 connectors

6 x SATA 6Gb/s connectors

1 x front panel header

1 x front panel audio header



1 x S/PDIF Out header

Vaš izbrani izdelek.

1 x USB Type-C® header, with USB 3.2 Gen 1 support

1 x USB 3.2 Gen 1 header

2 x USB 2.0/1.1 headers

1 x serial port header

2 x Thunderbolt™ add-in card connectors

1 x Trusted Platform Module header (For the GC-TPM2.0 SPI/GC-TPM2.0 SPI 2.0 module only)

1 x reset button

1 x Q-Flash Plus button

1 x reset jumper

1 x Clear CMOS jumper

ZUNANJI PRIKLJUČKI:

1 x USB Type-C® port, with USB 3.2 Gen 2x2 support

1 x USB 3.2 Gen 2 Type-A port (red)

4 x USB 3.2 Gen 1 ports

4 x USB 2.0/1.1 ports

2 x SMA antenna connectors (2T2R)

1 x HDMI 2.0 port

1 x DisplayPort

1 x RJ-45 port

3 x audio jacks

DODATNO:

iTE® I/O Controller Chip

H/W Monitoring

Voltage detection

Temperature detection

Fan speed detection

Water cooling flow rate detection

Fan fail warning

Fan speed control

BIOS

1 x 256 Mbit flash

Use of licensed AMI UEFI BIOS

PnP 1.0a, DMI 2.7, WfM 2.0, SM BIOS 2.7, ACPI 5.0

Unique Features

Support for GIGABYTE Control Center (GCC)



Support for Q-Flash

Vas izbrani izdelek.

Support for Q-Flash Plus

Support for Smart Backup

Bundled Software

Norton® Internet Security (OEM version)

LAN bandwidth management software

Spletna stran proizvajalca: <https://www.gigabyte.com/Motherboard/Z790-UD-rev-10#kf>