



 š izbrani izdelek.

## MIKROTIK HAP AC LITE USMERJEVALNIK (RB952UI-5AC2ND)

**ŠIFRA:** MITIK-0088  
**55.99€**

RB952UI-5AC2ND MIKROTIK 4752224003195

### DODATNE INFORMACIJE

|                              |                   |
|------------------------------|-------------------|
| <b>Weight</b>                | 0.4500 kg         |
| <b>Dimensions</b>            | 12 × 5.5 × 5.5 cm |
| <b>Garancija<br/>mesecih</b> | 12 mesecev        |
| <b>Proizvajalec</b>          | MIKROTIK          |



**Zaloga:** 4 na zalogi

**Kategorije:** [Mrežna oprema](#), [Usmerjevalniki](#)

### OPIS IZDELKA

HAP ac lite je dvojna sočasna dostopna točka, ki omogoča pokritje Wifi hkrati za frekvence 2,4GHz in 5GHz.

Enota je opremljena z 650MHz CPU, 64MB RAM-a, petimi 10 / 100Mbps Ethernet vrati (PoE izhod na vrata # 5), dvo verižnim brezžičnim 802.11b / g / n 2.4GHz brezžičnim omrežjem, eno verigo 802.11ac 5GHz brezžičnim omrežjem, USB vhodom za 3G / 4G modem in licenco RouterOS L4.



Mikrotik ima na voljo dve različici - RB952Ui-5ac2nD (International) in RB952Ui-5ac2nD-US (ZDA).  
Vas izbrani izdelek.  
RB952Ui-5ac2nD-US (ZDA) je tovarniško zaklenjen za frekvence 2412-2462MHz, 5150-5250MHz in 5725-5850MHz. Te ključavnice ni mogoče odstraniti. RB952Ui-5ac2nD (International) podpira območje 2412-2484MHz in 5150MHz - 5875MHz.

## Specifications

| Details                    |                          |
|----------------------------|--------------------------|
| Product code               | RB952Ui-5ac2nD           |
| Architecture               | MIPSBE                   |
| CPU                        | QCA9531                  |
| CPU core count             | 1                        |
| CPU nominal frequency      | 650 MHz                  |
| Dimensions                 | 113 x 89 x 28mm          |
| License level              | 4                        |
| Operating System           | <a href="#">RouterOS</a> |
| Size of RAM                | 64 MB                    |
| Storage size               | 16 MB                    |
| Storage type               | FLASH                    |
| Tested ambient temperature | -30°C to 70°C            |
| Suggested price            | \$49.95                  |

## Powering

| Details                                |                     |
|----------------------------------------|---------------------|
| PoE in                                 | Passive PoE         |
| PoE in input Voltage                   | 12-30 V             |
| PoE out                                | Passive PoE         |
| PoE-out ports                          | Ether5              |
| Number of DC inputs                    | 2 (DC jack, PoE-IN) |
| DC jack input Voltage                  | 10-30 V             |
| Max out per port output (input < 30 V) | 500 mA              |
| Max total out (A)                      | 500 mA              |
| Max power consumption                  | 8 W                 |



## Wireless

Vas izbrani izdelek.

| Details                           |              |
|-----------------------------------|--------------|
| AC speed                          | AC750        |
| Antenna gain dBi for 2.4 GHz      | 2            |
| Wireless 2.4 GHz standards        | 802.11b/g/n  |
| Wi-Fi generation                  | 5            |
| Wireless 2.4 GHz Max data rate    | 300 Mbit/s   |
| Wireless 5 GHz Max data rate      | 433 Mbit/s   |
| Wireless 2.4 GHz number of chains | 2            |
| Wireless 2.4 GHz chip model       | QCA9531      |
| Wireless 5 GHz number of chains   | 1            |
| Wireless 5 GHz standards          | 802.11a/n/ac |
| Antenna gain dBi for 5 GHz        | 2            |
| Wireless 5 GHz chip model         | QCA9887      |

## Ethernet

| Details               |   |
|-----------------------|---|
| 10/100 Ethernet ports | 5 |

## Peripherals

| Details             |            |
|---------------------|------------|
| Number of USB ports | 1          |
| USB Power Reset     | Yes        |
| USB slot type       | USB type A |
| Max USB current (A) | 1          |

Več na: [uradni strani](#)