



✓ Š izbrani izdelek.



MIKROTIK STIKALO 48 PORT CRS354-48P-4S+2Q+RM

ŠIFRA: MITIK-0060

955.99€

CRS354-48P-4S+2Q+RM MIKROTIK 4752224002273

DODATNE INFORMACIJE

Weight	8.6000 kg
Dimensions	4.4 × 44.3 × 44.3 cm
Garancija mesecih	12 mesecev
Proizvajalec	MIKROTIK



Zaloga: 1 na zalogi

Kategorije: [Mrežna oprema](#), [Stikala](#)



OPIS IZDELKA

Novi CRS354-48P-4S + 2Q + RM je učinkovita in prilagodljiva stojna rešitev za upravljanje omrežij v najzahtevnejših okoljih.

Za razliko od mnogih drugih stikal, so izdelki Mikrotik narejeni z mislijo na skrbnika sistema.



To močno stikalo ima 48 x 1G RJ45 vrat in 4 x 10G SFP + vrata ter tudi 2 x 40G QSFP + vrata za Vaš izbrani izdelek. izjemno hitre optične povezave ali povezovanje z drugimi napravami s hitrostjo 40 Gbps.

Vseh 48 mrežnih vrat ponuja različne možnosti izhodne moči: pasivni PoE, nizkonapetostni PoE, 802.3af / at (tip 1 "PoE" / tip 2 "PoE +") s samodejnim zaznavanjem, zaradi česar je to stikalo najlažja rešitev za napajanje tudi največjih porabnikov.

Vključen je mogočen napajalnik, ki lahko zagotavlja 750 W moči in poleg je še poseben nosilec za enostavno upravljanje kablov.

CRS354-48P-4S + 2Q + RM je izjemno funkcionalen in bo popoln dodatek k profesionalni uporabi omrežja.

Skupna pretočnost je 168 Gbps, preklopna zmogljivost je 336 Gbps, hitrost posredovanja pa 235 Mpps.

SPECIFIKACIJE:

Details	
Product code	CRS354-48P-4S+2Q+RM
Architecture	MIPSBE
CPU	QCA9531
CPU core count	1
CPU nominal frequency	650 MHz
Dimensions	443 x 382 x 44 mm
RouterOS license	5
Operating System	RouterOS
Size of RAM	64 MB
Storage size	16 MB
Storage type	FLASH
MTBF	Approximately 200'000 hours at 25C
Tested ambient temperature	-20°C to 60°C
Powering	
Details	
Number of AC inputs	1
AC input range	100-240
Max power consumption	800 W



Vaš

Max power consumption zbrani izdelek. without attachments	85 W
FAN count	4
PoE-out	
Details	
PoE-out ports	Ether1-Ether48
PoE out	802.3af/at
Max out per port output (input 18-30 V)	1000 mA
Max out per port output (input 30-57 V)	570 mA
Total output current	27A at 26V OR 13.2A at 53V
Total output power	700W
Ethernet	
Details	
10/100 Ethernet ports	1
10/100/1000 Ethernet ports	48
Fiber	
Details	
SFP+ ports	4
Number of 40G QSFP+ ports	2
Peripherals	
Details	
Serial console port	RJ45
Other	
Details	
CPU temperature monitor	Yes
Current Monitor	Yes
PCB temperature monitor	Yes
Voltage Monitor	Yes
Certification & Approvals	
Details	
Certification	CE, EAC, ROHS



Vaš izbrani izdelek.	IP IP20
----------------------	------------