



✓ Š izbrani izdelek.



MIKROTIK USMERJEVALNIK HEX POE RB960PGS


ŠIFRA: MITIK-0093

90.99€

RB960PGS MIKROTIK 4752224003294

DODATNE INFORMACIJE

Weight	0.8100 kg
Dimensions	11.4 × 2.9 × 2.9 cm
Garancija mesecih	12 mesecev
Proizvajalec	MIKROTIK



Zaloga: 6 na zalogi

Kategorije: [Mrežna oprema](#), [Usmerjevalniki](#)



OPIS IZDELKA

hEX PoE je 5 portni Gigabit Ethernet usmerjevalnik za lokacije, kjer brezžična povezava ni potrebna. Naprava ima vrata USB 2.0 in SFP vrata za dodajanje povezljivosti optičnih vlaken.

Vrata 2-5 lahko napajajo druge naprave, ki podpirajo PoE, z enako napetostjo kot na enoti.

Je cenovno ugoden, majhen in enostaven za uporabo, hkrati pa ima zelo zmogljiv 800MHz CPU, ki je



zmožen vseh naprednih konfiguracij, ki jih podpira RouterOS.

Vas izbrani izdelek.

Manj napajalnikov in kablov, ki vas skrbijo!

Največji tok je 1A na vrata, vrata Ethernet so zaščitena.

Podpira tudi pasivni PoE vhod in pasivni ali 802.3af / na PoE izhodu.

Ethernetna vrata 2-5 lahko napajajo druge naprave, ki podpirajo PoE, z enako napetostjo, kot je na enoti.

Če uporabljate vhodno napetost 48-57, lahko napaja naprave / af način B (4,5 +) (7,8-).

SPECIFIKACIJE

Details	
Product code	RB960PGS
Architecture	MIPSBE
CPU	QCA9557
CPU core count	1
CPU nominal frequency	800 MHz
RouterOS license	4
Operating System	RouterOS
Size of RAM	128 MB
Storage size	16 MB
Storage type	FLASH
MTBF	Approximately 100'000 hours at 25C
Tested ambient temperature	-40°C to 60°C
Suggested price	\$79.00
Powering	
Details	
Number of DC inputs	2 (DC jack, PoE-IN)
DC jack input Voltage	12-57 V
Max power consumption	54 W
Max power consumption without attachments	6 W
FAN count	Passive
PoE in	Passive PoE
PoE in input Voltage	12-57 V



Vaš

PoE-out	
Details	
PoE-out ports	Ether2-Ether5
PoE out	802.3af/at
Max out per port output (input 18-30 V)	1:00 dop.
Max out per port output (input 30-57 V)	450 mA
Max total out (A)	2:00 dop.
Ethernet	
Details	
10/100/1000 Ethernet ports	5
Fiber	
Details	
SFP ports	1
Peripherals	
Details	
Number of USB ports	1
USB Power Reset	Yes
USB slot type	USB type A
Max USB current (A)	1
Other	
Details	
PCB temperature monitor	Yes
Voltage Monitor	Yes
Certification & Approvals	
Details	
Certification	CE, EAC, ROHS
IP	IP20