



Veš izbrani izdelek.



MIKROTIK WAP AC LTE6 DOSTOPNA TOČKA

ŠIFRA: MITIK-0057

206.99€

RBwAPGR-5HacD2HnD&R11e-LTE6 MIKROTIK
4752224004925

DODATNE INFORMACIJE

Weight	0.8150 kg
Dimensions	3 × 15.5 × 15.5 cm
Garancija mesecih	12 mesecev
Proizvajalec	MIKROTIK



Zaloga: 2 na zalogi

Kategorije: [Mrežna oprema](#), [Usmerjevalniki](#)



OPIS IZDELKA

Majhen paket z velikimi ambicijami – komplet wAP ac LTE6 je nadgradnja izjemno stroškovno učinkovite dvopasovne (2,4 / 5 GHz) domače dostopne točke, ki temelji na priljubljeni vremensko odporni obliki wAP.



Njegov novi modem CAT6 LTE omogoča še večjo hitrost prenosa – do 300 Mbps!

Vaš izbrani izdelek.

CAT6 omogoča tudi združevanje nosilcev in omogoča napravi, da uporablja več pasov hkrati.

Velika prednost, ko je na območju veliko uporabnikov LTE.

Zagotavlja boljšo odzivnost v gneči in večjo učinkovitost pri šibkejšem signalu na podežlju.

Komplet WAP ac LTE6 ima dva gigabitna ethernetna priključka – napravo lahko uporabljate kot žični usmerjevalnik z varnostno kopijo LTE prek reže za mikro SIM.

Druga možnost je, da lahko uživajte v gladki brezžični izkušnji kjer koli – v zaprtih prostorih ali na prostem.

WAP ac LTE je zasnovan za zagotavljanje močne in zanesljive povezave v skoraj vseh razmerah in vremenskih razmerah.

Prenese temperature od -30 C° do +60 C° in se enostavno namesti na stene, stropne ali stebre.

Specifications	
Details	
Product code	RBwAPGR-5HacD2HnD&R11e-LTE6
Architecture	ARM 32bit
CPU	IPQ-4018
CPU core count	4
CPU nominal frequency	716 MHz
Switch chip model	IPQ-4018
RouterOS license	4
Operating System	RouterOS
Size of RAM	128 MB
Storage size	16 MB
Storage type	FLASH
MTBF	Approximately 100'000 hours at 25C
Tested ambient temperature	-30°C to 60°C
IPsec hardware acceleration	Yes
Powering	
Details	
Number of DC inputs	2 (DC jack, PoE-IN)



Vaš
izbrani izdelek

DC jack input Voltage	10-57 V
Max power consumption	16 W
Max power consumption without attachments	10 W
Cooling type	Passive
PoE in	802.3af/at
PoE in input Voltage	18-57 V
Mobile	
Details	
2G Category	Class12
2G bands	2 (1900MHz) / 3 (1800MHz) / 5 (850MHz) / 8 (900MHz)
3G Category	R7 (21Mbps Downlinks, 5.76Mbps Uplink) / R8 (42.2Mbps Downlink, 5.76Mbps Uplink)
3G bands	1 (2100MHz) / 2 (1900MHz) / 5 (850MHz) / 8 (900MHz)
LTE Category	6 (300Mbit/s Downlink, 50Mbit/s Uplink)
LTE FDD bands	1 (2100MHz) / 2 (1900MHz) / 3 (1800MHz) / 7 (2600MHz) / 8 (900 MHz) / 20 (800MHz) / 5 (850MHz) / 12 (700MHz) / 17 (700MHz) / 25 (1900MHz) / 26 (850MHz)
LTE TDD bands	38 (2600MHz) / 40 (2300MHz) / 39 (1900MHz) / 41n (2500MHz)
Wireless specifications	
Details	
Wireless 2.4 GHz Max data rate	300 Mbit/s
Wireless 2.4 GHz number of chains	2
Wireless 2.4 GHz standards	802.11b/g/n
Antenna gain dBi for 2.4 GHz	2.maj



Vaš
izbrani izdelek

Wireless 2.4 GHz chip model	IPQ-4018
Wireless 2.4 GHz generation	Wi-Fi 4
Wireless 5 GHz Max data rate	867 Mbit/s
Wireless 5 GHz number of chains	2
Wireless 5 GHz standards	802.11a/n/ac
Antenna gain dBi for 5 GHz	2.maj
Wireless 5 GHz chip model	IPQ-4018
Wireless 5 GHz generation	Wi-Fi 5
Ethernet	
Details	
10/100/1000 Ethernet ports	2
Peripherals	
Details	
Number of SIM slots	1 Modem (Micro SIM)
MiniPCI-e slots	1
Other	
Details	
PCB temperature monitor	Yes
Voltage Monitor	Yes
Certification & Approvals	
Details	
Certification	CE, FCC, IC, EAC, ROHS
IP	IP54