



Več informacij



TP-LINK 2.4GHZ 300MBPS 12DBI ZUNANJA CPE


ŠIFRA: TPLNC-CPE220

54.99€

CPE220 TP-LINK 6935364091583

DODATNE INFORMACIJE

Weight	1.1000 kg
Dimensions	10.5 × 32.5 × 32.5 cm
Garancija mesecih	36 mesecev
Proizvajalec	TP-LINK



Zaloga: 6 na zalogi

Kategorije: [Mrežna oprema](#), [Usmerjevalniki](#)





OPIS IZDELKA

HARDWARE FEATURES

Processor	Qualcomm Atheros 560MHz CPU, MIPS 24Kc
Memory	64MB DDR2 RAM, 8MB Flash
Interface	1 10/100Mbps Shielded Ethernet Port (LAN0, Passive PoE in) 1 10/100Mbps Shielded Ethernet Port (LAN1) 1 Grounding Terminal 1 Reset Button
Power Supply	Passive Power over Ethernet via LAN0 (+4,5pins; -7,8pins) Voltage range: 16-27VDC 10.8 Watts Max
Power Consumption	Note: When deployed using Passive PoE, the power drawn from the power source will be higher by some amount depending on the length of the connecting cable.
Dimensions (W x D x H)	11×3.1×2.1 inch (276×79×60 mm)
Antenna Type	Built-in 12dBi 2x2 Dual-polarized Directional Antenna Beam Width: 60° (H-Plane) / 30° (E-Plane) Note: For more details, please refer to datasheet
Protection	15KV ESD Protection 6KV Lightning Protection
Enclosure	Outdoor ASA stabilized plastic material IPX5 waterproof Certification

WIRELESS FEATURES

Wireless Standards	IEEE 802.11b/g/n (with Pharos MAXtream disabled)
---------------------------	--



Vaš izbrani izdelek.

WIRELESS FEATURES

Proprietary Protocol

TDMA Mode (with Pharos MAXtream enabled)

Wireless Speeds

Up to 300Mbps (40MHz,Dynamic)

Up to 144.4Mbps (20MHz,Dynamic)

Up to 72.2Mbps (10MHz,Dynamic)

Up to 36.1Mbps (5MHz,Dynamic)

2.4~2.483GHz

Frequency

Note: Available operating frequency may vary depending on the limitations

of the countries or regions in which the device is used.

30dBm/1000mw (Adjustable power by 1dBm)

Transmission Power

Note: Maximum transmission power may vary across different channels depending

on the limitations of the countries or regions in which the device is used.

SOFTWARE FEATURES

Pharos MAXtream TDMA Technology

802.11b/g/n Modes

Selectable Channel Width: 5/10/20/40MHz

Automatic Channel Selection

Transmission Power Control

Dynamic Frequency Selection (DFS)

WDS Enable/Disable

Security: WPA/WPA2, WPA-PSK/WPA2-PSK (AES/TKIP)

Wireless Configurations

Encryption, 64/128/152-bit WEP Encryption

SSID Broadcast Enable/Disable

Multi-SSID with VLAN Tagging (AP mode only)

Distance/ACK Timeout Setting

Wireless MAC Address Filter

Wireless Advanced:

> Beacon Interval/RTS Threshold/Fragmentation

>Threshold/DTIM Interval/AP Isolation/Short GI/Wi-Fi

Multimedia



Vaš izbrani izdelek.

SOFTWARE FEATURES

Management	Discovery and Remote Management via Pharos Control application HTTP/HTTPS Web-based management System Log SNMP Agent(v2c) Ping Watch Dog Dynamic DDNS SSH Server
System Tools	Wireless Signal Quality Indicators: Signal Strength/Noise/Transmit CCQ/CPU/Memory Monitors: Throughput/Stations/Interfaces/ARP/Routes/WAN/DHCP Spectrum Analyzer Speed Test Ping Traceroute
System-level Optimizations	Optimized IGMP Snooping/Proxy for multicast applications Hardware watch dog

POE ADAPTER FEATURES

Dimensions(W x D x H)	85.8×43.9×31.9 mm
Interfaces	1 AC Jack with Earth Ground 1 10/100/1000Mbps Shielded Ethernet Port (Power + Data) 1 10/100/1000Mbps Shielded Ethernet Port (Data)
Button	Remote Reset Button
Power Status LEDs	Green
Input	100-240VAC, 50/60Hz 24VDC, 0.5A Max
Output	+4, 5pins; -7, 8pins. (Support up to 60m Power over Ethernet)
Efficiency	>80%
Certifications	CE/FCC/UL/IC/GS/PSB/C-tick/SAA/S-Mark/KC-mark



Vaš izbrani izdelek.

OTHERS

Certification

CE, FCC, RoHS, IPX5

Package Contents

Outdoor Wireless CPE

24V 0.5A Passive PoE Adapter

Pole Mounting Straps

AC Power Cord

Installation Guide

System Requirements

Microsoft Windows 98SE, NT, 2000, XP, Vista™ or Windows 10, Windows 8, Windows 7,

MAC OS, NetWare, UNIX or Linux.

Note: We recommend you to use one of following Web browsers for an improved user

experience: Google Chrome, Safari, and Firefox. IE browsers are not recommended.

Environment

Operating Temperature: -40°C~70°C (-40°F~158°F)

Storage Temperature: -40°C~70°C (-40°F~158°F)

Operating Humidity: 10%~90% non-condensing

Storage Humidity: 5%~95% non-condensing

Spletna stran izdelka:

<https://www.tp-link.com/en/business-networking/outdoor-radio/cpe220/#overview>