



 Š izbrani izdelek.

## TP-LINK 24-PORT 10/100MBPS RACKMOUNT STIKALO

**ŠIFRA:** TPLNC-TL\_SF1024  
**59.99€**

TL-SF1024 TP-LINK 6935364021474

### DODATNE INFORMACIJE

<b>Weight</b>	1.0000 kg
<b>Dimensions</b>	18 × 4.5 × 4.5 cm
<b>Garancija mesecih</b>	36 mesecev
<b>Proizvajalec</b>	TP-LINK



**Zaloga:** 1 na zalogi

**Kategorije:** [Mrežna oprema](#), [Stikala](#)

## OPIS IZDELKA

### HARDWARE FEATURES

Standards and Protocols

IEEE 802.3i, IEEE 802.3u, IEEE  
802.3x



## HARDWARE FEATURES

Interface	24 10/100Mbps RJ45 Ports (Auto Negotiation/Auto MDI/MDIX)
Network Media	10BASE-T: UTP category 3, 4, 5 cable (maximum 100m) 100BASE-TX: UTP category 5, 5e or above cable (maximum 100m)
Fan Quantity	Fanless
Power Supply	100-240VAC, 50/60Hz
Power Consumption	Maximum: 3.53W (220V/50Hz)
Dimensions ( W x D x H )	17.3*7.1*1.7 in. (440*180*44 mm)
Mounting	Rack Mountable
Max Power Consumption	3.19W(220V/50Hz)
Max Heat Dissipation	10.88BTU/h

## PERFORMANCE

Switching Capacity	4.8Gbps
Packet Forwarding Rate	3.57Mpps
MAC Address Table	8K
Buffer Memory	2Mb



## PERFORMANCE

Green Technology	Innovative energy-efficient technology saves power up to 75%
Transfer Method	Store-and-Forward

## OTHERS

Certification	FCC, CE, RoHS
Package Contents	24-Port 10/100Mbps Rackmount Switch Power Cord Installation Guide Rackmount Kit Rubber Feet
System Requirements	Microsoft® Windows® 8, 7, Vista™, XP or MAC® OS, NetWare®, UNIX® or Linux.
Environment	Operating Temperature: 0°C~40°C (32°F~104°F); Storage Temperature: -40°C~70°C (-40°F~158°F); Operating Humidity: 10%~90% non-condensing; Storage Humidity: 5%~90% non-condensing

Več na: <https://www.tp-link.com/se/service-provider/unmanaged-switch/tl-sf1024/#overview>