



✓ Š izbrani izdelek.



TP-LINK 8-PORT 10/100MBPS NAMIZNO STIKALO S 4 PORTI POE

ŠIFRA: TPLNC-TL_SF1008P

57.99€

TL-SF1008P TP-LINK 6935364021665

DODATNE INFORMACIJE

Weight	0.3900 kg
Dimensions	27 × 180 × 180 cm
Garancija mesecih	36 mesecev
Proizvajalec	TP-LINK



Zaloga: 5 na zalogi

Kategorije: [Mrežna oprema](#), [Stikala](#)



OPIS IZDELKA



HARDWARE FEATURES

Interface	8 10/100Mbps RJ45 Ports AUTO Negotiation/AUTO MDI/MDIX
Network Media	10BASE-T: UTP category 3, 4, 5 cable (maximum 100m) EIA/TIA-568 100Ω STP (maximum 100m) 100BASE-TX: UTP category 5, 5e cable (maximum 100m) EIA/TIA-568 100Ω STP (maximum 100m)
Fan Quantity	Fanless
Power Consumption	Maximum (PoE on): 60.2W (220V/50Hz) Maximum (PoE off): 3.2W (220V/50Hz)
External Power Supply	External Power Adapter(Output: 48VDC / 1.25A)
PoE Ports (RJ45)	Standard: 802.3 af compliant PoE Ports: Port1- Port4 Power Supply: 57W
Backbound Bandwidth	1.6Gbps
Mac Address Table	2K
Dimensions (W x D x H)	6.7*3.9*1.1 in. (171*98*27 mm)



HARDWARE FEATURES

Max Power Consumption	2.66(220/50Hz. no PD connected) 65.92(220/50Hz. with 57W PD connected)
Max Heat Dissipation	9.08BTU/h(no PD connected) 224.92BTU/h(with 57W PD connected)

SOFTWARE FEATURES

Transmission Method	Store-And-Forward
Advanced Functions	Compatible With IEEE 802.3af Compliant PDs Priority Function Mac Address Auto-Learning And Auto-Aging IEEE802.3x Flow Control For Full-Duplex Mode And Backpressure For Half-Duplex Mode

OTHERS

Certification	FCC, CE, RoHS
Package Contents	TL-SF1008P, Power Adapter, User Guide



OTHERS

Consumption	2.3 watts (max. no PD connected) 59.3 watts (max. with 57w PD connected)
Environment	Operating Temperature: 0°C~40°C (32°F~104°F) Storage Temperature: -40°C~70°C (-40°F~158°F) Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~90% non-condensing

Več na: <https://www.tp-link.com/se/business-networking/unmanaged-switch/tl-sf1008p/#overview>