



Š izbrani izdelek.



## TP-LINK ARCHER T2U NANO 600MBPS BREŽIČNA USB MREŽNA KARTICA


ŠIFRA: TPLNC-ARCHER\_T2U\_2

9.99€

Archer T2U Nano TP-LINK 6935364099978

### DODATNE INFORMACIJE

<b>Weight</b>	0.2000 kg
<b>Dimensions</b>	2 × 1.5 × 1.5 cm
<b>Garancija mesecih</b>	36 mesecev
<b>Proizvajalec</b>	TP-LINK



Zaloga: 10 na zalogi

Kategorije: [Mrežna oprema](#), [Mrežne kartice](#)



## OPIS IZDELKA

### Wireless Standards

### WIRELESS FEATURES

IEEE 802.11ac, IEEE 802.11a,  
IEEE 802.11n, IEEE 802.11g, IEEE 802.11b



Vaš izbrani izdelek.

## WIRELESS FEATURES

<b>Frequency</b>	5GHz 2.4GHz
<b>Signal Rate</b>	5GHz 11ac: Up to 433Mbps(dynamic) 11n: Up to 150Mbps(dynamic) 11a: Up to 54Mbps(dynamic) 2.4GHz 11n: Up to 200Mbps(dynamic) 11g: Up to 54Mbps(dynamic) 11b: Up to 11Mbps(dynamic)
<b>Reception Sensitivity</b>	5GHz: 11a 6Mbps: -90dBm 11a 54Mbps: -73dBm 11n HT20 MCS0: -89dBm 11n HT20 MCS7: -70dBm 11n HT40 MCS0: -86dBm 11n HT40 MCS7: -67dBm 11ac VHT80 MCS0: -82dBm 11ac VHT80 MCS9: -56dBm 2.4GHz: 11b 1Mbps: -96dBm 11b 11Mbps: -88dBm 11g 6Mbps: -89dBm 11g 54Mbps: -74dBm 11n HT20 MCS0: -89dBm 11n HT20 MCS7: -72dBm 11n HT40 MCS0: -86dBm 11n HT40 MCS7: -66dBm
<b>Transmit Power</b>	<20dBm (EIRP)
<b>Wireless Modes</b>	Ad-Hoc / Infrastructure mode
<b>Wireless Security</b>	Support 64/128 bit WEP, WPA-PSK/WPA2-PSK, 802.1x
<b>Modulation Technology</b>	DBPSK, DQPSK, CCK, OFDM, 16-QAM, 64-QAM, 256-QAM

## OTHERS



Vaš izbrani izdelek.

## **OTHERS**

### **Certification**

CE, FCC, RoHS

### **Package Contents**

AC600 Nano Wireless USB Adapter Archer T2U Nano  
Resource CD  
Quick Installation Guide

### **System Requirements**

Windows 10/8.1/8/7/XP (32/64bits),  
Mac OS X 10.9-10.13

### **Environment**

Operating Temperature: 0°C~40°C (32°F~104°F)  
Storage Temperature: -40°C~70°C (-40°F~158°F)  
Operating Humidity: 10%~90% non-condensing  
Storage Humidity: 5%~90% non-condensing

## **HARDWARE FEATURES**

### **Interface**

USB 2.0

### **Dimensions ( W x D x H )**

15\*7.1\*18.6mm

### **Antenna Type**

Omni Directional