



✓ Š izbrani izdelek.



TP-LINK USMERJEVALNIK ARCHER AX73 AX5400 DUAL BAND GIGABIT USMERJEVALNIK WI-FI 6

ŠIFRA: TPLNC-ARCHER_AX73

122.99€

ARCHER AX73 TP-LINK 6935364010263

DODATNE INFORMACIJE

Weight 1.2000 kg

**Garancija
mesecih** 36 mesecev

Proizvajalec TP-LINK



Zaloga: 10 na zalogi

Kategorije: [Mrežna oprema](#), [Usmerjevalniki](#)



OPIS IZDELKA

Gigabitni Wi-Fi 6 hitrosti naslednje generacije – 4804 Mbps pri 5 GHz in 574 Mbps v pasu 2,4 GHz zagotavlja gladko pretakanje in hitrejše prenose

Poveži več naprav – tehnologija OFDMA poveča zmogljivost za 4-krat, da omogoči hkratni prenos na več naprav



Ultra-nizka zakasnitev - omogoča bolj odzivno igranje iger in video klepetanje

Vaš izbrani izdelek.

Razširjena pokritost Wi-Fi - štiri zunanje antene z visokim izkoristkom in tehnologija Beamforming skupaj razširijo močan in zanesljiv Wi-Fi po vsem vašem domu

TP-Link HomeShield - Izboljšana varnost ščiti pred najnovejšimi kibernetскими grožnjami

OneMesh - Brez zamenjave obstoječih naprav ali nakupa popolnoma novega ekosistema WiFi vam

OneMesh pomaga ustvariti bolj prilagodljivo omrežje, ki pokriva celoten dom z izdelki TP-Link

OneMesh

Standards Wi-Fi 6

IEEE 802.11ax/ac/n/a 5 GHz

IEEE 802.11ax/n/b/g 2.4 GHz

WiFi Speeds AX5400

5 GHz: 4804 Mbps (802.11ax, HE160)

2.4 GHz: 574 Mbps (802.11ax)

WiFi Range 3 Bedroom Houses

6x Fixed High-Performance Antennas

Multiple antennas form a signal-boosting array to cover more directions and large areas

Beamforming

Concentrates wireless signal strength towards clients to expand WiFi range

High-Power FEM

Improves transmission power to strengthen signal coverage

4T4R

Multiple streams in the same band strengthen the fault tolerance in transmission

WiFi Capacity High

Dual-Band

Allocate devices to different bands for optimal performance

4x4 MU-MIMO

Simultaneously communicates with multiple MU-MIMO clients

OFDMA

Simultaneously communicates with multiple Wi-Fi 6 clients

Airtime Fairness

Improves network efficiency by limiting excessive occupation



DFS

Vaš izbrani izdelek.

Access an extra band to reduce congestion

6 Streams

Connect your devices to more bandwidth

Working Modes Router Mode

Access Point Mode

HARDWARE

Processor 1.5 GHz Triple-Core CPU

Ethernet Ports 1× Gigabit WAN Port

4× Gigabit LAN Ports

Static Link Aggregation (LAG) available with 2× LAN ports

USB Support 1× USB 3.0 Port

Supported Partition Formats:

NTFS, exFAT, HFS+, FAT32

Supported Functions:

Apple Time Machine

FTP Server

Media Server

Samba Server

Buttons Wi-Fi On/Off Button

Power On/Off Button

LED On/Off Button

WPS Button

Reset Button

Power 12 V === 2.5 A

SECURITY

WiFi Encryption WPA

WPA2

WPA3

WPA/WPA2-Enterprise (802.1x)

Network Security SPI Firewall

Access Control

IP & MAC Binding

Application Layer Gateway



HomeShield Security

Vas izbrani izdelek.

Real-Time IoT Protection

Malicious Site Blocker

Intrusion Prevention System

DDoS Attack Prevention

Home Network Scanner

Guest Network 1× 5 GHz Guest Network

1× 2.4 GHz Guest Network

VPN Server OpenVPN

PPTP

SOFTWARE

Protocols IPv4

IPv6

Service Kits HomeShield

Learn More>

OneMesh™ OneMesh™ Supported

Without replacing your existing devices or buying a whole new WiFi ecosystem, OneMesh™ helps you create a more flexible network that covers your entire home with TP-Link OneMesh™ products.

Learn More>

All OneMesh Products>

Parental Controls HomeShield Parental Controls

Custom Profiles

Professional Content Filter Library

Family Time

Bedtime

Off Time

Time Rewards

Family Online Time Ranking

Pause the Internet

Weekly and Monthly Reports

WAN Types Dynamic IP

Static IP

PPPoE

PPTP

L2TP

Quality of Service QoS by Device

Cloud Service Auto Firmware Upgrade



TP-Link ID
Vaš izbrani izdelek.
DDNS

NAT Forwarding Port Forwarding

Port Triggering

DMZ

UPnP

Virtual Server

IPTV IGMP Proxy

IGMP Snooping

Bridge

Tag VLAN

DHCP Address Reservation

DHCP Client List

Server

DDNS TP-Link

NO-IP

DynDNS

Management Tether App

Webpage

PHYSICAL

Dimensions (W×D×H) 10.7 × 5.8 × 1.9 in

(272.5 × 147.2 × 49.2 mm)

Package Contents Wi-Fi Router Archer AX73

Power Adapter

RJ45 Ethernet Cable

Quick Installation Guide

OTHER

System Requirements Internet Explorer 11+, Firefox 12.0+, Chrome 20.0+, Safari 4.0+, or other JavaScript-enabled browser

Cable or DSL Modem (if needed)

Subscription with an internet service provider (for internet access)

Certifications FCC, CE, RoHS

Environment Operating Temperature: 0°C~40°C (32°F ~104°F)

Storage Temperature: -40°C~70°C (-40°F ~158°F)

Operating Humidity: 10%~90% non-condensing

Storage Humidity: 5%~90% non-condensing



TEST DATA

Vaš izbrani izdelek:

WiFi Transmission Power CE:

<20dBm{2.4GHz}

<23dBm{5.15GHz~5.35GHz}

<30dBm{5.47GHz~5.725GHz}

FCC:

<24dBm{5.25GHz~5.35GHz&5.47GHz~5.725GHz }

<30dBm{2.4GHz &5.15GHz~5.25GHz&5.725GHz~5.825GHz }

WiFi Reception Sensitivity 2.4GHz:

11ac VHT20 MCS0:-94.5dBm

11ac VHT20 MCS8:-72.5dBm

11ac VHT40 MCS0:-92.5dBm

11ac VHT40 MCS9:-69.5dBm

11ax HE20 MCS0:-95dBm

11ax HE20 MCS11:-64.5dBm

11ax HE40 MCS0:-92.5dBm

11ax HE40 MCS11:-62dBm

5GHz:

11ac VHT20 MCS0:-97dBm

11ac VHT20 MCS8:-74dBm

11ac VHT40 MCS0:-95dBm

11ac VHT40 MCS9:-70dBm

11ac VHT80 MCS0:-91.5dBm

11ac VHT80 MCS9:-66dBm

11ac VHT160 MCS0:-86dBm

11ac VHT160 MCS9:-61dBm

11ax HE20 MCS0:-95dBm

11ax HE20 MCS11:-64dBm

11ax HE40 MCS0:-91.5dBm

11ax HE40 MCS11:-62dBm

11ax HE80 MCS0:-88dBm

11ax HE80 MCS11:-58dBm

11ax HE160 MCS0:-85.5dBm

11ax HE160 MCS11:-55dBm