



✓ š izbrani izdelek.



TP-LINK VIGI 3MP SMART IR ZUNANJA NADZORNA KAMERA (DO 2304X1296 H.265+ IN 30FPS)

ŠIFRA: TPLNC-VIGIC300HP4

40.99€

VIGI C300HP-4 TP-LINK 6935364072254

DODATNE INFORMACIJE

Weight	0.5000 kg
Dimensions	12 × 9 × 9 cm
Garancija mesecih	36 mesecev
Proizvajalec	TP-LINK



Zaloga: 9 na zalogi

Kategorije: [Dom in vrt](#), [Kamere](#), [Pametni dom](#)



OPIS IZDELKA

Security

NETWORK

Password Protection, HTTPS Encryption, IP Address Filter,
Digest Authentication



Vaš izbrani izdelek.

NETWORK

Protocol	TCP/IP, UDP, ICMP, HTTP, HTTPS, DHCP, DNS, RTSP, NTP, UPnP UDP, SSL/TLS
API	ONVIF
Simultaneous Live View	4 Main Streams & 3 Sub-Streams, or 3 Main Streams & 5 Sub-Streams

GENERAL

Package Contents	VIGI Network Camera Quick Start Guide Waterproof Cable Attachments Mounting Bracket Mounting Accessories (Screws, Drywall Anchors, Hex Key)
Operating Temperature	-30-60 °C
Certifications	CE, FCC, RCM, BSMI, VCCI, IP67, RoHS
Dimensions(H X W X D)	164.9 × 87.4 × 83.4 mm
Material	Plastic
Weight	283.5g
General Features	Two Streams, Mirror, Privacy Masks, Password Reset via E-mail, HTTP Listening
Power Requirements	12V DC ± 5%, 5.5mm Coaxial Power Plug PoE (802.3af/at, class 0)

CAMERA

Image Sensor	1/2.8" Progressive Scan CMOS
Lens	4 mm / 6 mm
Aperture	4 mm: F2.4 6 mm: F2.0
Lens Mount	M12
Viewing Angle	(4 mm) horizontal FOV: 82.5°, vertical FOV: 44.9°, diagonal FOV: 99.3° (6 mm) horizontal FOV: 51.9°, vertical FOV: 28.7°, diagonal FOV: 60°
Day/Night Mechanism	IR Cut Filter



Vaš izbrani izdelek.

CAMERA

IR Working Distance	30m
Minimum Illumination	Color: 0.1 Lux@F2.0; 0 Lux with IR
Weatherproof Rating	IP67
Digital Noise Reduction	3D DNR
WDR	DWDR

VIDEO/IMAGE

Video Compression	Main stream: H.265/H.264 Sub-Stream: H.265/H.264
Frame Rate & Resolutions	Frame Rate: 1fps, 5fps, 10fps, 15fps, 20fps, 25fps, 30fps Resolution: 2304x1296, 2048x1280, 1920x1080, 1280x720, 704x576, 640x480, 352x288, 320x240
Video Streaming	Main Stream Sub-Stream
Image Settings	Mirror, Brightness, Contrast, Saturation, Sharpness, Exposure, WDR, White Balance Adjustable by Client Software
Image Enhancement	BLC/3D DNR/Prevent Overexposure to Infrared Light
Video Bit Rate	64 Kbps to 6 Mbps

SMART FEATURE-SET

Smart Event	Area Intrusion Detection, Line-Crossing Detection
Basic Event	Motion Detection, Camera Tampering Detection, Exception (illegal login)
Linkage Method	Trigger Notification: ONVIF, HTTPS
Region of Interest	1 Region

INTERFACES

Network Interface	1 RJ45 10/100M Self-Adaptive Ethernet Port
Alarm	-
Button	-
Video Output	-