



✓ Š izbrani izdelek.



## UBIQUITI 24 PORT USW-PRO-24-POE MREŽNO STIKALO, 400W

ŠIFRA: UBINT-0095

**813.99€**

USW-PRO-24-POE UBIQUITI 817882027649

### DODATNE INFORMACIJE

<b>Weight</b>	4.9000 kg
<b>Dimensions</b>	5 x 40 x 40 cm
<b>Garancija mesecih</b>	12 mesecev
<b>Proizvajalec</b>	UBIQUITI



**Zaloga:** 6 na zalogi

**Kategorije:** [Mrežna oprema](#), [Stikala](#)



### OPIS IZDELKA

24-portno stikalo s (16) 802.3at PoE + vrati, (8) 802,3bt PoE ++ vrati in (2) 10 GB SFP + vrati. Zmogljivo preklapljanje UniFi druge generacije!

UniFi Switch Pro 24 PoE je popolnoma upravljano stikalo Layer 3 z (8) 802.3bt (PoE ++) in (16)



802.3at (PoE +) Gigabit Ethernet vrati.

Vas izbrani izdelek.

2) Povezave 10G SFP + ponujajo združevanje povezav za večjo zmogljivost in večjo razpoložljivost.

UniFi Switch Pro 24 PoE ima bogat nabor možnosti Layer 2 in vključuje funkcije Layer 3, kot so usmerjanje med VLAN, statično usmerjanje in strežnik DHCP.

Omrežni krmilnik UniFi in mobilna aplikacija UniFi Network skrbnikom omogočata konfiguriranje in spremljanje tako rekoč vseh funkcij stikal v intuitivnem grafičnem uporabniškem vmesniku od koder koli.

### Lastnosti:

(8) Gigabitna vrata RJ45 802,3bt PoE ++

(16) Gigabitna vrata RJ45 802.3at PoE +

(2) 10G SFP + vrata

Funkcije sloja 2 in sloja 3

400 W največja moč PoE

UniFi SmartPower RPS DC vhod

Skoraj tiho hlajenje

1,3-palčni zaslon na dotik

Upravljanje preko UniFi Network Controller programske opreme

Mechanical	
Dimensions	442.4 x 285.4 x 43.7 mm (17.42 x 11.24 x 1.72")
Weight	4.30 kg (9.48 lb)
With Rackmount Brackets	4.39 kg (9.68 lb)
Interfaces	(24) 10/100/1000 RJ45 Ports
Networking	(2) 1/10G SFP+ Ethernet Ports
Management	Ethernet In-Band
Power Method	
Universal Input	100-240VAC/50-60 Hz
USP RPS DC Input	52VDC, 7.69A; 11.5VDC, 2.61A
Power Supply	AC/DC, Internal, 450W
Supported Voltage Range	100 to 240VAC
Max. Power Consumption (Excluding PoE Output)	50W
LEDs	



Vaš

System zbrani izdelek	Status
RJ45 Data Ports	PoE; Speed/Link/Activity
SFP Data Ports	Link/Activity
ESD/EMP Protection	Air: $\pm 16$ kV, Contact: $\pm 12$ kV
Shock and Vibration	ETSI300-019-1.4 Standard
Operating Temperature	-5 to 40° C (23 to 104° F)
Operating Humidity	10 to 90% Noncondensing
Certifications	CE, FCC, IC
Sound Level*	
25% PoE Load, 25° C Room Temperature	0.9 dBr
50% PoE Load, 25° C Room Temperature	7.3 dBr
100% PoE Load, 40° C	18.8 dBr
PoE	
PoE Interfaces	
Ports 1-16	POE+ IEEE 802.3af/at, (pins 1, 2+; 3, 6-)
Ports 17-24	60W PoE++ IEEE 802.3bt, (Pair A 1, 2+; 3, 6-) (Pair B 4, 5+; 7, 8-)
Max. PoE Wattage per Port by PSE	
802.3at	32W
802.3bt	64W
Voltage Range 802.3af Mode	44-57V
Voltage Range 802.3at Mode	50-57V