



Š izbrani izdelek.



UBIQUITI GIGABITNI POE ADAPTER POE-24-24W-G


ŠIFRA: UBINT-0100

15.99€

POE-24-24W-G UBIQUITI 810354023538

DODATNE INFORMACIJE

Weight	0.1600 kg
Dimensions	4 × 9 × 9 cm
Garancija mesecih	12 mesecev
Proizvajalec	UBIQUITI



Zaloga: 3 na zalogi

Kategorije: [Mrežna oprema](#), [PoE](#)



OPIS IZDELKA

Ubiquiti PoE adapterji nudijo različne funkcije za zaščito vaših naprav PoE:

- Prenapetostna zaščita
- Zaščita pred vpenjanjem
- Največja prenapetostna razelektritev



- Najvišji impulzni tok
Vaš izbrani izdelek.
- AC kabel z ozemljitvijo

Elektrostatična razelektritev (ESD) je glavni vzrok za okvare zunanjih naprav.

Z ozemljenim adapterjem Ubiquiti PoE, TOUGH Cable™ in TOUGH Cable konektorji se lahko učinkovito zaščitite pred poškodbami zaradi ESD.

Specifikacije	
Model	POE-24-24W-G
Dimensions	88 x 57 x 33 mm (3.47 x 2.24 x 1.30")
Weight	158.5 g (5.59 oz)
Output Voltage	24VDC @ 1.0A
LAN Activity Indicator	No
Gigabit LAN Port	Yes
Remote Reset Capability	Yes
Reset Button	Yes
Rated Voltage	100-240VAC @ 50/60Hz
Input Current	0.6A @ 120VAC, 0.4A @ 240VAC
Inrush Current	<60A Peak @ 120VAC, <120A Peak @ 230VAC
Efficiency	80+%
Output Ripple	1% Max.
Switching Frequency	65 kHz
Line Regulation	≤ 3%
Load Regulation	≤ 5%
2-Pair Powering	Pins 4, 5 (+) and Pins 7, 8 (-)
4-Pair Powering	-
Operating Temperature	0 to 40° C (32 to 104° F)
Storage Temperature	-30 to 70°C (-22 to 158° F)
Operating Humidity	35 to 95% Noncondensing
AC Connector	IEC-320 C6
Data IN / PoE	RJ45 Shielded Socket
Surge Protection	Difference and Common Mode
Clamping Protection	11V Data, 60V Power
Max. Surge Discharge	1500A (8/20 μs) Power



Vaš izbrani izdelek	Peak Pulse Current	36A (10/1000 μ s) Data
	Shunt Capacitance	<5 pF data
	Response Time	<1 ns
	Certifications	CE, FCC, IC, UL