

š izbrani izdelek.



## UBIQUITI LITE 8 PORT, 4X POE GIGABITNO MREŽNO STIKALO

ŠIFRA: UBINT-0105

**129.99€**

USW-Lite-8-POE UBIQUITI 810010071156

### DODATNE INFORMACIJE

<b>Weight</b>	0.4800 kg
<b>Dimensions</b>	8.4 × 14.7 × 14.7 cm
<b>Garancija mesecih</b>	12 mesecev
<b>Proizvajalec</b>	UBIQUITI



**Zaloga:** 2 na zalogi

**Kategorije:** [Mrežna oprema](#), [Stikala](#)



### OPIS IZDELKA

Popolnoma upravljano stikalo Layer 2 z (8) gigabitnimi Ethernet vrati v kompaktni obliki. USW-Lite-8-PoE je popolnoma upravljano stikalo Layer 2 z osmimi gigabitnimi Ethernet vrati za vaše RJ45 Ethernet naprave.



Štiri vrata ponujajo tudi samodejno zaznavanje PoE + 802.3at, ki zagotavlja skupno moč PoE 52 W za Vas izbrani izdelek.  
dostopne točke UniFi ali druge naprave PoE.

USW-Lite-8-PoE, ki ga upravlja in konfigurira aplikacija UniFi Network s podporo za mobilne aplikacije UniFi, ponuja protokole in funkcije za preklapljanje na ravni 2.

Aplikacija UniFi Network in mobilna aplikacija skrbnikom omogočata konfiguriranje in spremljanje tako rekoč vseh funkcij stikal v grafičnem uporabniškem vmesniku iz kjerkoli.

### Lastnosti:

- (8x) Gigabitna vrata RJ45, vključno s (4x) 802.3af / na vratih PoE +
- Upravlja se z različico aplikacije UniFi: 5.13.10 ali novejša
- Zunanji 60W napajalnik
- Možna montaža na steno (komplet priložen )
- Upravlja se z različico omrežne aplikacije UniFi: 5.13.10 ali novejša

### Specifikacije:

Mechanical	
Dimensions	99.6 x 163.7 x 31.7 mm (3.92 x 6.44 x 1.25")
Weight	450 g (15.87 oz)
Hardware	
Total Non-Blocking Line Rate	8 Gbps
Max. Power Consumption	8W
Power Method	54VDC, 1.1A Power Adapter
Power Supply	External 54V/60W Power Adapter
Supported Voltage Range	DC 50V to 57V
Networking Interfaces	(8) 10/100/1000 Mbps Ethernet RJ45 Ports
PoE Interfaces	(4) PoE+ IEEE 802.3af/at (Pins 1, 2+; 3, 6-)
Management Interface	Ethernet In-Band
Max. PoE+ Wattage per Port by PSE	30W
Modes	SMB Layer 2 PoE Gigabit Ethernet Switch
Operating Temperature	-15 to 40° C (5 to 104° F)
Operating Humidity	10 - 90% Noncondensing
Certifications	CE, FCC, IC
LEDs	



Vaš izbrani izdelek.  System	(1) Power, Blue/White
	Flashing White: Bootup in Progress
	Flashing Blue: Firmware Upgrading
	Steady White: Factory Defaults, Awaiting Adoption
	Steady Blue: Device is Adopted
Ethernet	Green: 1G, Amber: 10/100 Mbps
PoE	Amber: IEEE 802.3af/at