



✓ Š izbrani izdelek.



UBIQUITI STIKALO 48 PORT USW-48-POE

ŠIFRA: UBINT-0109

684.99€

USW-48-POE UBIQUITI 810010072146

DODATNE INFORMACIJE

Weight	5.0000 kg
Dimensions	28.5 × 4.37 × 4.37 cm
Garancija mesecih	12 mesecev
Proizvajalec	UBIQUITI



Zaloga: 2 na zalogi

Kategorije: [Mrežna oprema](#), [Stikala](#)



OPIS IZDELKA

Layer 2, stikalo PoE z (48) vrati GbE RJ45, vključno z (32) vrati PoE+ in (4) vrati 1G SFP.

Stikalo 48 PoE (USW 48 PoE) je popolnoma upravljano stikalo z (48) vrati GbE RJ45, vključno z (32) vrati GbE, PoE+ in (4) vrati 1G SFP.



Vsestranski USW 48 PoE zagotavlja povezave Gigabit PoE do ethernetnih naprav, hkrati pa nudi možnost povezave z gigabitnimi optičnimi vlakni, primerne za omrežje podjetij.

Stikalo ponuja tudi obsežen nabor preklonnih protokolov ravni 2, vključno z načini delovanja, specifičnimi za vrata (preklapljanje, zrcaljenje ali združevanje), in ima 1,3-palčni barvni zaslon na dotik LCM, ki jedrnato prikazuje ključne vpogleda v sistem in povezavo.

To stikalo je lahko tudi spremljati ali konfigurirati od koder koli z zmogljivo in intuitivno spletno aplikacijo UniFi Network in mobilno aplikacijo.

Lastnosti:

(1) 1,3-palčni barvni zaslon na dotik LCM z upravljanjem stikal AR

(32) vrata GbE, PoE+ RJ45

(16) Vrata GbE RJ45

(4) 1G SFP vrata

Skupna moč 195 W PoE

Tiho hlajenje brez ventilatorja

Upravlja se z aplikacijo UniFi Network: različica 5.12.32 in novejša

TEHNIČNE SPECIFIKACIJE:

Mechanical	
Dimensions	442.4 x 285 x 43.7 mm (17.42 x 11.22 x 1.72")
Weight	Without: Rackmount Brackets 4.52 kg (9.97 lb)
	With Rackmount Brackets: 4.61 kg (10.16 lb)
Hardware	
Networking Interface	(48) 10/100/1000 RJ45 Ports
	(4) 1G SFP Ethernet Ports
Management Interface	Ethernet In-Band
Total Non-Blocking Throughput	52 Gbps
Switching Capacity	104 Gbps
Forwarding Rate	77.38 Mpps
Power Method	100-240VAC, 50/60 Hz, Universal Input
Power Supply	AC/DC, Internal, 240W



Vaš

Supported Voltage Range	100 to 240VAC
Max. Power Consumption	45W
(Excluding PoE Output)	
LEDs	
RJ45 Data Ports	PoE; Speed/Link/Activity
SFP Data Ports	Link/Activity
ESD/EMP Protection	Air: ± 16 kV, Contact: ± 12 kV
Shock and Vibration	ETSI300-019-1.4 Standard
Operating Temperature	-5 to 40° C (23 to 104° F)
Operating Humidity	10 to 90% Noncondensing
Certifications	CE, FCC, IC
PoE	
Total Available PoE	195W
PoE Interfaces	PoE/PoE+ (Pins 1, 2+; 3, 6-)
Ports 1-32	
Max. PoE Wattage per Port by PSE	32W
PoE+	
Voltage Range PoE Mode	44-57V
Voltage Range PoE+ Mode	50-57V